

STAR WARS® REBEL ASSAULT™

REFERENCE CARD

CONTENTS

Your *Rebel Assault* package should contain the following items:

- One Compact Disc
- This Reference Card
- One User's Manual
- Odds 'n ends that you don't really need to play the game

READ ME

Additional information on setting up and playing the game may be found in your READ ME file. To access this file, change directories to your CD drive and, at the prompt, type: **README**. To advance to the next screen of the READ ME file, press the SPACEBAR.

How to make a basic BOOT Disk to run a CD-based game

Note: In all of the following sections, read an underscore (_) as a space.

- **First, you will need to format a floppy disk and make it bootable.**

1) Insert a new, unformatted floppy disk into your **A:** drive.

2) At your **C:** prompt, type:

format_A:_/s <enter>

This will format the floppy disk and tell the operating system that this disk can be booted from.

3) At your **C:** prompt, type:

dir_A: <enter>

A list of files on the newly formatted floppy disk will appear. Look for a file called **COMMAND.COM**. If you do not find one, you will need to copy it to the floppy from your hard drive by typing at the **C:** prompt:

copy_command.com_A: <enter>

If you get an error message that the copy command cannot find **COMMAND.COM**, it might be because the file has been moved to your DOS directory. Copy it from there by typing:

copy_dos\command.com_A: <enter>

- **Now you need to tell the boot floppy how to talk to your CD drive.**

The system gets this information from two files: **CONFIG.SYS** and **AUTOEXEC.BAT**. You will need to create these two files on your boot floppy, using the two versions on your hard drive as reference.

4) At your **C:** prompt, type:

copy_config.sys_a: <enter>

copy_autoexec.bat_a: <enter>

This will copy the two files from your hard drive to the floppy disk.

5) At your **C:** prompt, type:

a: <enter>

This changes your current drive from your **C:** drive to your **A:** drive. Your **C:** prompt should change to **A:**. **IMPORTANT!** Verify that your prompt has changed to **A:**. You will be modifying your **CONFIG.SYS** and **AUTOEXEC.BAT** files on the floppy disk. If you fail to change drives first, you will change the files on your hard disk instead and may make your hard disk unbootable.

6) At your **A:** prompt, type:

edit_config.sys <enter>

You will now be running the DOS text editor, which you may use to modify the **CONFIG.SYS** file. Move your cursor around the file with the arrow keys. You can insert text at the cursor location by simply typing it, or delete the character currently over the cursor by pressing the <delete> key.

7) On your floppy disk, delete non-essential lines from the **CONFIG.SYS** file by moving the cursor to the beginning of the line and pressing delete several times. Keep any lines relating to your CD drive and sound card. Unfortunately, exactly what lines you will need to keep will vary slightly depending on what hardware you have installed in your machine. When you are done, your file should look something like this:

LASTDRIVE = E

DEVICE = C:\DOS\HIMEM.SYS

DEVICE = C:\SCSI\MA13B.SYS

DEVICE = C:\SCSI\NECCDR.SYS /D:NECCD

DEVICE = C:\SBPRO\DRV\SBPCD.SYS /D:MSCD001 /P:220

DOS = HIGH

DOS = UMB

BUFFERS = 20

FILES = 20

DEVICE = C:\DOS\SETVER.EXE

The above example is for a computer set up for an NEC CD-ROM drive with a Sound Blaster Pro sound card. For your setup, the lines in italics may be completely different, and there may be more or fewer lines. Look for and keep lines that list your CD-drive's name, sound card's name, or "CD" in them somewhere.

8) Hold down the <alt> key and press **F** simultaneously. Then press the **X** key. This will allow you to save your changes and exit the text editor.

9) At your **A:** prompt, type:

edit_autoexec.bat <enter>

You will be running the DOS text editor, which you may use to modify the **AUTOEXEC.BAT** file.

10) On your floppy disk, delete non-essential lines from the **AUTOEXEC.BAT** file. Keep any lines referring to your sound card, CD drive or mouse (if you plan to play *Rebel Assault* with a mouse) Again, exactly what lines you will need to keep will vary slightly depending on what hardware you have installed in your machine. When you are done, your file should look something like this:

@ECHO OFF

C:\SCSI\MSCDEX /D:NECCD /M:10 /L:d /V

PROMPT \$P\$G

SET TEMP=C:\DOS


SET BLASTER=A220 I7 D1 T4

SET SOUND=C:\SBPRO

PATH=C:\;C:\DOS;C:\SCSI;C:\WINDOWS

C:\WINDOWS\MOUSE.COM /Y

Again, the lines in italics may vary greatly from those shown, depending



on your particular hardware and how it is configured. Other lines may vary slightly.

11) Save your changes and exit the text editor as before.

12) Try out your boot disk.

You can now cold boot your computer with this disk in your **A:** drive. To cold boot, take all disks out of disk drives. Manually turn off the computer using the main switch. Wait for the machine to stop running. Put the boot disk into the **A:** drive. Switch on the machine.

If your boot disk does not work you may have deleted lines necessary for your particular system. Remove the boot floppy, boot from your hard disk and repeat the process. If you have questions, refer to your sound card and CD-ROM manuals or contact their technical support departments.

How to Disable Memory Managers

You may be able to temporarily disable your memory manager at boot time without resorting to a boot disk. To safely disable the memory managers found on your computer, follow these instructions:

Emm386® If you are using a version of DOS 5.0, you must either make a system boot disk **without** the Emm386.exe device line, or temporarily comment out the line with runs Emm386 from your **CONFIG.SYS** file. Do this by using **EDIT** and insert the letters **REM** before the line which looks either like:

DEVICE = c:\dos\emm386.exe

or

DEVICE = c:\windows\emm386.exe

Once changed, the lines will look like:

REM_DEVICE = c:\dos\emm386.exe

or

REM_DEVICE = c:\windows\emm386.exe

After making a change, you will need to reboot for the changes to take effect.

If you are using a version of DOS 6.0, you can selectively choose which lines to run at boot time. Do this by rebooting your computer and holding down the **F8 key** as the computer boots up.

386Max® Before turning on the computer, hold down the **<alt> key**. Keep the key depressed while the system boots to disable the memory manager

QEMM® Before turning on the computer, hold down the **<alt> key**. Keep the key depressed while the system boots to disable the memory manager

NetRoom® Before turning on the computer, hold down the **<ctrl> key**. Keep the key depressed while the system boots to disable the memory manager

Rebel Assault TM and © 1993 LucasArts Entertainment Company. Used Under Authorization. All Rights Reserved. Star Wars is a registered trademark of Lucasfilm Ltd. The LucasArts logo is a registered service mark of LucasArts Entertainment Company. LucasArts is a trademark of LucasArts Entertainment Company. IBM is a registered trademark of International Business Machines. All other trademarks are hereby acknowledged as the proprietary property of their respective owners. LucasArts Entertainment Company, P.O. Box 10307, San Rafael, CA 94912